

Gree Gama Caseta de tavan R32



Unitate exterioara			GUD50W/NhA-T	GUD71W/NhA-T	GUD100W/NhA-T	GUD125W/NhA-T	GUD140W/NhA-T
Unitate interioara			GUD50T/A-T	GU71T/A-T	GUD100T/A-T	GUD125T/A-T	GUD140T/A-T
Funcție			Racire/Incalzire	Racire/Incalzire	Racire/Incalzire	Racire/Incalzire	Racire/Incalzire
Capacitate	Racire	KW	1.6/5.0/4.5	2.4/7.0/8.0	3.2/10.0/11.0	3.6/12.10/12.8	6.0/13.4/14.2
		BTU/h	5459/17000/15354	8188/23800/27296	10918/34100/37532	12283/41200/43673	20472/45700/48450
	Incalzire	KW	1.5/5.5/6	2.2/8.0/9.0	3.0/12.0/13.5	3.6/13.50/14.5	3.9/15.50/16.0
		BTU/h	5118/18700/2472	7506/27200/30708	10236/40900/46062	12283/46000/49474	13306/52800/54592
SEER/SCOP		W/W	6.9/4.0	7.2/3.9	6.1/4.0	6.1/3.8	6.1/3.6
Clasa de energie	Racire / Incalzire		A+ / A+	A++ / A	A++ / A+	A++ / A	A++ / A+
Alimentare electrica		Ph-V-Hz	1 Ph-220V-240V-50Hz	1 Ph-220V-240V-50Hz	1 Ph-220V-240V-50Hz	1 Ph-220V-240V-50Hz	1 Ph-220V-240V-50Hz
Putere electrica consumata	Racire nom	Kw	1.55	2.1	3.2	4.1	4.45
	Incalzire nom	Kw	1.45	2.25	3.4	4.1	4.6
Domeniu temperatura exterior de functionare	Racire	°C	-20°C ~ 48°C	-20°C ~ 48°C	-20°C ~ 48°C	-20°C ~ 48°C	-20°C ~ 48°C
	Incalzire	°C	-20°C ~ 24°C	-20°C ~ 24°C	-20°C ~ 24°C	-20°C ~ 24°C	-20°C ~ 24°C
Unitate Interioara							
Nivel de presiune acustica	SH/H/M/L	dB/A	39/36/33	42/40/39	48/46/42	49/46/42	51/48/45
Debit de aer		m3/h	700/580/480/400	1100/1050/960/870	1500/1470/1380/1220	1800/1690/1470/1260	1900/1690/1480/1140
Dimensiune carcasa	LxIxA	mm	570×570×265	840×840×240	840×840×240	840×840×290	840×840×290
Dimensiuni ambalaj	LxIxA	mm	688×643×295	963×963×325	963×963×325	963×963×379	963×963×379
Greutate	neta/bruta	Kg	17 / 22	29 / 36	31 / 38	33 / 41	36 / 44
Unitate Exterioara							
Dimensiune carcasa	LxIxA	mm	818×302×596	892×340×698	940×460×820	940×460×820	940×460×820
Dimensiuni ambalaj	LxIxA	mm	948×420×645	1029×458×750	1073×563×868	1073×563×868	1073×563×868
Greutate	neta/bruta	Kg	39 / 42	53 / 57	83 / 95	91 / 103	95 / 107
Nivel de presiune acustica		dB/A	53	52	55	55	56
Tevi conexiun	gaz	mm	6.35	9.52	9.52	9.52	9.52
	lichid	mm	12.7	15.9	15.9	15.9	15.9
Traseu maxim	inaltime	m	20	25	30	30	30
	lungime	m	35	50	65	75	75
Refrigerant			R32	R32	R32	R32	R32
Panel							
Dimensiune carcasa	LxIxA	mm	620×620×47.5	950×950×52	950×950×52	950×950×52	950×950×52
Dimensiuni ambalaj	LxIxA	mm	701×701×125	1033×1038×112	1033×1038×112	1033×1038×112	1033×1038×112
Greutate	neta	Kg	4.5	9.5	9.5	9.5	9.5