

Fisa tehnica Gree Bora A4

| Model | | | GWH09AAB-K3DNA4A* | GWH12AAB-K3DNA4A* | GWH18AAD-K3DNA4E | GWH24AAD-K3DNA4A |
|--|---------------------|---------|---------------------|---------------------|---------------------|---------------------|
| Functie | | | Racire / Incalzire | Racire / Incalzire | Racire / Incalzire | Racire / Incalzire |
| Capacitate | Racire | Btu/h | 1700/8530/11500 | 2050/10920/12290 | 2220/15700/17750 | 5970/21000/21500 |
| | Incalzire (min/max) | Btu/h | 1700/8530/12000 | 2050/11260/12970 | 2390/17060/18000 | 5970/21150/23030 |
| Putere alimentare | Racire (min/max) | W | 160/790/1350 | 120/995/1400 | 150/1430/1860 | 450/2000/2200 |
| | Incalzire (min/max) | W | 200/650/1450 | 120/1000/1500 | 160/1380/1680 | 450/1900/2430 |
| Curent nominal | Racire (min/max) | A | 3.45 | 4.4 | 6.34 | 9.35 |
| | Incalzire (min/max) | A | 2.95 | 4.4 | 6.12 | 10 |
| Alimentare | | Ph-V-Hz | 220-240V~ 50Hz, 1Ph | 220-240V~ 50Hz, 1Ph | 220-240V~ 50Hz, 1Ph | 220-240V~ 50Hz, 1Ph |
| SEER/SCOP | | W/W | 6.10/ 4.0 | 6.10/ 4.0 | 6.10/ 4.0 | 6.10/ 4.0 |
| Clasa de eficienta Energetica | Racire | | A++ | A++ | A++ | A++ |
| | Incalzire | | A+ | A+ | A+ | A+ |
| Unitate interioara | | | | | | |
| Debit (SH/H/M/L) | | m3/h | 550/500/430/300 | 550/500/430/300 | 850/720/610/520 | 850/720/610/520 |
| Nivel de presiune sonora (SH/H/M/L) | | dB(A) | 40/37/35/28 | 40/36/33/29 | 45/42/37/33 | 47/43/39/34 |
| Nivel de putere sonora (SH/H/M/L) | | dB(A) | 54/49/47/40 | 55/48/45/41 | 58/53/50/45 | 59/55/51/46 |
| Dimensiune carcasa (L*A*I) | | mm | 773x250x185 | 773x250x185 | 970x300x225 | 970x300x225 |
| Greutate neta/bruta | | Kg | 8.5/9.5 | 8.5/9.5 | 13.5/16.5 | 13.5/16.5 |
| Unitate exterioara | | | | | | |
| Nivel de presiune sonora/putere sonora | | dB(A) | 50 / 60 | 52 / 62 | 54 / 63 | 57 / 67 |
| Dimensiune carcasa (L*A*I) | | mm | 776x540x320 | 848x596x320 | 842x596x320 | 955x700x396 |
| Greutate neta/bruta | | Kg | 26/28.5 | 31 / 34 | 33/36 | 46/50.5 |
| Conexiuni tevi lichid / gaz | | mm | 6/9.52 | 6 / 9.52 | 6 / 9.52 | 6 / 16 |
| Lungime max. traseu/ Dif. Max. traseu | | m | 15 / 10 | 20 / 10 | 20 / 10 | 25 / 10 |
| Interval functionare racire/incalzire | | ° C | -15 ~ 43/-15 ~ 24 | -15 ~ 43/-15 ~ 24 | -15 ~ 48/-15 ~ 24 | -15 ~ 43/-15 ~ 24 |

*au kit de instalare inclus